

Technical data IMPRESSA X9 Win

Key features

| | |
|--|---|
| Latte macchiato and cappuccino at the press of a button | ■ |
| Total of 10 product keys can be individually assigned | ■ |
| Pot coffee in espresso quality | ■ |
| Auto cappuccino for frothy milk | ■ |
| Auto cappuccino for hot milk | ■ |
| Separate hot water and steam outlet | ■ |
| Pour coffee and hot water or steam simultaneously | ■ |
| 3.5 inch multicolour TFT display | ■ |
| Video and audio-aided operation | ■ |
| Microsoft Windows CE-based operating system | ■ |
| Two separate heater systems | ■ |
| Active bean monitoring | ■ |
| Cup rail | ■ |
| Automatic milk rinsing | ■ |
| Integrated combination cleaning (milk and coffee system) | ■ |
| User identification through code | ■ |
| Cup counter with individual reset facility | ■ |
| TÜV certificate for user-friendly manual | ■ |
| Maintenance status can be called up at any time | ■ |

IMPRESSA key technologies and standards

| | |
|---|---|
| Intelligent Pre Brew Aroma System (I.P.B.A.S.®) | ■ |
| CLARIS plus filter cartridge (I.P.W.S.® compatible) | ■ |
| 2 cups in one brewing cycle | ■ |
| 6 stage high performance conical grinder | ■ |
| Thermoblock heater system | ■ |
| 2 high performance pumps each 15 bar | ■ |
| Indicator display for water filter | ■ |
| Indicator display for maintenance programme | ■ |
| Power switch | ■ |

Programming

| | |
|--|---|
| Programmable coffee mixture | ■ |
| Programmable brewing temperature | ■ |
| Programmable coffee water quantity | ■ |
| Programmable hot water quantity | ■ |
| Programmable shut-off time by week day | ■ |
| Programmable switch on time by week day | ■ |
| Auto cut-off | ■ |
| Integrated flushing / cleaning / decalcification programme | ■ |
| Programmable water hardness | ■ |

Preparation times

| | |
|--|---------|
| 1 espresso (45 ml) approx. | 30 sec. |
| 2 espressos approx. | 45 sec. |
| 1 coffee (120 ml) approx. | 40 sec. |
| 2 coffees approx. | 65 sec. |
| 1 cappuccino (100 ml coffee) approx. | 40 sec. |
| 1 coffee with milk (100 ml coffee) approx. | 40 sec. |
| 1 latte macchiato (45 ml coffee) approx. | 40 sec. |


Capacity

| | |
|---------------------------------|----------------|
| Daily capacity | up to 100 cups |
| Bean containers | 650 g each |
| Coffee set container (portions) | max. 40 |
| Water tank capacity | 5.0 l |
| Hot water output | 10 l/hr. |

Available accessories (optional)

| | |
|--|---|
| Milk cooler | ■ |
| Cup warmer | ■ |
| Choco module | ■ |
| Connection to mains water supply | ■ |
| Catering mobile unit / catering module | ■ |
| Modular box – accounting system | ■ |
| MDB interface | ■ |

Facts and figures

| | |
|---------------------------------|--|
| Variable brewing chamber | 5–16 g |
| Height adjustable coffee outlet | 60–142 mm |
| Weight | 20.7 kg |
| Dimensions (W x H x D) | 43 x 58 x 51 cm |
| Cable length | 1.8 m |
| Amperage | 15 A |
| Voltage | 230 V AC |
| Output | 2200 W |
| Tests | CE  |
| Article number EU | 13458 |
| EAN-Code EU | 7610917134588 |
| Swiss made | ■ |